



NEW PRODUCT

NPR_2201

OEX Submersible Bilge Pumps

OEX bilge pumps are fitted with ball bearing enabling the motors to be rated continuously thus preventing burn out from dry running. All pumps are both CE and EMC approved and are supplied with a stainless steel hose clamp.

550GPH Bilge Pump

- Outlet Dia: 29mm
- Delivery Volume: 550GPH
- Delivery Head: 3.8M
- Voltage: DC12V
- Current: 2.5A (12V)
- Rating: Continuous
- Cable Length: .75M
- Water Temp: 0 - 60 Degree
- CE/EMC Approval

PART NO. MCX001



1000GPH Bilge Pump

- Outlet Dia: 29.5mm
- Delivery Volume: 1000GPH
- Delivery Head: 4M
- Voltage: DC12V
- Current: 5.5A (12V)
- Rating: Continuous
- Motor Power: 45W / 5500RPM
- Weight: 1.7kgs
- Cable Length: 1.2M
- Standard Accessory: ELBOW
- Water Temp: 0 - 60 Degree
- CE/EMC Approval

PART NO. MCX003



1500GPH Bilge Pump

- Outlet Dia: 28.5mm
- Delivery Volume: 1500GPH
- Delivery Head: 4M
- Voltage: DC12V
- Current: 8A (12V)
- Rating: Continuous
- Motor Power: 75W / 5500RPM
- Weight: 2.4kgs
- Cable Length: 1.2M
- Standard Accessory: ELBOW
- Water Temp: 0 - 60 Degree
- CE/EMC Approval

PART NO. MCX005



2000GPH Bilge Pump

- Outlet Dia: 28.5mm
- Delivery Volume: 2000GPH
- Delivery Head: 4M
- Voltage: DC12V
- Current: 11A (12V)
- Rating: Continuous
- Motor Power: 85W / 7000RPM
- Weight: 2.6kgs
- Cable Length: 1.2M
- Standard Accessory: ELBOW
- Water Temp: 0 - 60 Degree
- CE/EMC Approval

PART NO. MCX007



Visit www.ashdown-ingram.com.au
or www.ashdown-ingram.co.nz

Copyright © 2009 Ashdown Ingram

ashdown
ingram