

# OEX LIGHTING BY LABCRAFT



Labcraft is a market leader for high performance commercial vehicle LED and fluorescent lighting. By utilising the latest low energy technology, Labcraft lights can reduce the power consumption by more than 50% whilst offering up to 6 times more light than a standard bulb.

## LED LIGHTING

### Nebula

- 12 Volt
- 30 LEDs
- Tough aluminium weatherproof casing
- Ideal for refrigerated environments
- Temperature range from -30 - + 40°

(LIX00102)



### Powerlux

- 12 - 24 Volt
- 5 x 1.25 Watt LEDs
- Slim profile
- Waterproof IP67
- 100,000 hour life expectancy

(LIX00101)



### Astro

- 12 Volt
- 30 LED's
- Weatherproof casing
- Ideal for awning light solution
- Temperature range from -30 - + 40°

(LIX00103)



### Locker Lite

- 12 Volt
- Wire free
- Runs on 2 x 3 Volt lithium batteries
- On off plunger system
- Ideal for lockers, cupboards and wardrobes

(LIX00105)



### Spiro

- 12 Volt
- Waterproof
- Swivel housing
- Ideal for caravan bathroom and kitchen lighting
- Tough polycarbonate lens

(LIX00104)



# OEX

by

**Labcraft**  
DESIGN LED LIGHTING

Visit [www.ashdown-ingram.com.au](http://www.ashdown-ingram.com.au)

Copyright © 2008 Ashdown Ingram

ashdown  
ingram

# OEX LIGHTING BY LABCRAFT



## FLUORESCENT LIGHTING

### Frigospot

- Available in 12 Volt fluro and 12 Volt LED
- Ideal for refrigerated vehicles
- Epoxy powder coated, galvanised steel housing
- IP66 seal between housing and polycarbonate lens

(LIX11101 – Fluro) ▼

(LIX11102 – LED) ▼



### Recessed Batten Light

- 12 Volt
- Polycarbonate lens
- Over ¼ million switch cycles without causing tube failure
- Finished in corrosion proof paint
- Temperature range from -30 - +40°

(LIX11103)



### Opal

- 12 and 24 Volt available
- Weather proof
- Moulded from polycarbonate for strength
- Temperature range from -30 - +40°

(LIX11105 – 12 Volt) ▼

(LIX12105 – 24 Volt) ▼



### Crystalite

- 12 and 24 Volt models available
- Fabricated aluminium chassis
- Slimline design (34mm)

(LIX11106 – 12 Volt) ▼

(LIX12106 – 24 Volt) ▼



### Trillite

- 12 and 24 Volt models available
- Extremely low profile (24mm)
- Temperature range from -30 - +40°

(LIX11104 – 12 Volt) ▼

(LIX12104 – 24 Volt) ▼



### Square Light

- 12 and 24 Volt models available
- High light output (1,000 lumens)
- Polycarbonate construction
- Temperature range from -10 - +40°

(LIX11107 – 12 Volt) ▼

(LIX12107 – 24 Volt) ▼



Visit [www.ashdown-ingram.com.au](http://www.ashdown-ingram.com.au)

Copyright © 2008 Ashdown Ingram

ashdown  
ingram